

# Specifications

## Finished Frame Widths

<b>SINGLE HINGED</b>	<i>Net Frame Width</i>	<b>DOUBLE HINGED</b>	<i>Net Frame Width</i>	<b>GARDEN VENTING</b>	<i>Net Frame Width</i>
2/6 + 2/6	63"	2/6 + 2/6	62 1/4"	2/6 + 2/6	63"
2/8 + 2/8	67"	2/8 + 2/8	66 1/4"	2/8 + 2/8	67"
2/10 + 2/10	71"	2/10 + 2/10	70 1/4"	2/10 + 2/10	71"
3/0 + 3/0	75"	3/0 + 3/0	74 1/4"	3/0 + 3/0	75"

## Finished Frame Heights

<b>INSWING</b>	<i>Net Frame Height</i>
6/8	81 3/4"
8/0	97 3/4"

---

<b>OUTSWING</b>	<i>Net Frame Height</i>
6/8	80 3/4"
8/0	96 3/4"

\* 8/0 height is only available in a fiberglass door and composite frame option.

\* Renovator Garden Doors are available in steel doors and wood frame option. Refer to the Entry Garden Door Program.

\* Garden Venting in 6/8 outswing only.

## Rough Opening Measurements (RO)

Add 1" to width of net frame

Add 1/2" to height of net frame

For 14" transom, add 15-3/4" to height of net frame.

## Outside Measurements of Brickmould (OSM)

Add 2-1/2" to width of net frame

Add 1-1/4" to height of net frame

